



DB28XP

Technical specifications

Name: DB28XP
Reference: DB28XPTIS1
Function: Hours, Minutes
Movement: DB2115v6

Type: Mechanical hand-wound movement

Adjustment: Winding and setting the time by means of the crown (2)

positions)

Technical features of calibre DB2115v6

Number of parts: 194

Jewelling: 29 jewels Diameter: 30 mm

Power reserve: 6 days, ensured by a self-regulating twin barrel –

De Bethune Innovation (2004)



DE BETHUNE

L'ART HORLOGER AU XXIE SIÈCLE

Specificities: Titanium balance with white gold inserts, optimised for

temperature differences and air penetration -

De Bethune Patent (2016)

"De Bethune" balance-spring with flat terminal curve –

De Bethune Patent (2006)

Silicon escape wheel

Triple pare-chute shock-absorbing system –

De Bethune Innovation (2005)

Frequency: 28,800 vibrations/hour

Adornment: Hand-crafted finishing and decoration

Display

Display: Polished titanium hands with polished blued titanium

inserts

Dial: Polished titanium hours ring with polished titanium spherical

hour-markers

Circular satin-brushed titanium minutes ring

Polished titanium barrel bridge and triangular central bridge guards with straight-grained chamfered contours Titanium dial base with "microlight" decoration centred on

the balance – De Bethune Innovation (2007)

Case and strap

Case material: Polished grade 5 titanium with "microlight" case middle

Case diameter: 43 mm Case thickness: 7.2 mm

Lugs: Polished grade 5 titanium floating lugs –

De Bethune Patent (2006)

Crystal: Sapphire (1,800 Vickers hardness) with double anti-

reflective coating

Caseback: Solid, in polished grade 5 titanium

Engraved ring in blued circular satin-finish titanium Titanium plate with "microlight" decoration and De

Bethune logo

Water resistance: 3 ATM

Strap: Extra-supple alligator leather with alligator lining

Buckle: Grade 5 titanium buckle and pin