

DB28 Kind of Gold

USA Limited Edition





DB28 Kind of Gold USA Limited Edition

Technical specifications

Name: DB28 Kind of Gold, USA Limited Edition

Reference: DB28BRUS

Vintage: Production limited to 10 numbered pieces

Functions: Hours, Minutes, Spherical moon phase at 6

o'clock. Power reserve on case back, Performance

indicator between 2 and 3 o'clock

Movement: DB2115

Type: Mechanical hand-wound movement

Adjustment: Using the crown (2 positions) for winding, and

setting the time

Using a corrector for the spherical moon phase

Technical features of calibre DB2115

Number of parts: 297

Jewelling: 39 jewels Diameter: 30 mm

Power reserve: 6 days, ensured by a self-regulating twin barrel

De Bethune Innovation (2004)

Technical features: Titanium balance wheel with white gold inserts,

optimised for temperature differences and air

penetration

De Bethune Patent (2016)

"De Bethune" balance-spring with flat terminal

curve

De Bethune Patent (2006)

Silicon escape wheel

Spherical moon phase indicator with precision of one lunar day every 122 years – De Bethune Patent

(2004)

Blued triple pare-chute shock-absorbing system

De Bethune Innovation (2005)

Frequency: 28,800 vibrations per hour



Adornment: Handmade, blued grade 5 mirror-polished titanium

motion works bridge

Plate cover and bridge cover on the barrel in grade 5 blued titanium, adorned with "Côtes De

Bethune"

Barrels decorated with rose-work grinding

Power reserve indicator in grade 5 titanium, hand decorated with "De Bethune" concentric graining

and blued by hand

Steel parts beveled, polished and flame-blued by

hand

Display

Display: 5N Rose gold hands

Spherical moon phase indicator in rose gold and flame-blued steel with precision of one lunar day every 122 years at 6 o'clock – De Bethune Patent

(2004)

Performance indicator between 2 and 3 o'clock

Dial: Blued grade 5 polished titanium hours ring with

rose gold hour-markers

Blued grade 5 satin-polished titanium minutes ring

Case and strap

Case material: 5N Rose gold

Case diameter: 43 mm
Case thickness: 9.30 mm

Lugs: Short or long floating lugs in blued grade 5 mirror-

polished titanium – De Bethune Patent (2006)

Crystal: Sapphire (1800 Vickers hardness), with double

anti-reflective coating

Case back: Screwed case back in blued grade 5 polished

titanium that opens on a linear power reserve indicator in rose gold Sapphire crystal (1800 Vickers hardness) with double anti-reflective

coating

Water resistance: 3 ATM

Strap: Extra-supple alligator leather, alligator lining
Buckle: Buckle in blued grade 5 mirror-polished titanium

and ardillon in 5N rose gold