



DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

DB28 Maxichrono

Technical specifications





DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

DB28 Maxichrono

Technical specifications

| | |
|-------------|--|
| Name: | DB28 Maxichrono |
| Reference: | DB28MCTN / S |
| Limitation: | Limited annual production of 20 pieces |
| Functions: | Hours, Minutes, Mono-pusher chronograph with 24 hours, 60 minutes, 60 seconds |
| Movement: | DB2030 |
| Type: | Mechanical hand-wound movement |
| Adjustment: | By the crown (2 positions) for winding and setting the time Via a push-piece integrated in the crown for the chronograph function |

Technical features of calibre DB2030

| | |
|------------------|--|
| Number of parts: | 426 |
| Jewelling: | 51 jewels |
| Diameter: | 30 mm |
| Power reserve: | 5 days, ensured by a self-regulating twin barrel <i>De Bethune Innovation (2004)</i> |
| Specificities: | Silicon annular balance encircled by a white gold ring <i>De Bethune Patent (2010)</i> "De Bethune" balance-spring with flat terminal curve <i>De Bethune Patent (2006)</i> Silicon escape wheel "De Bethune Absolute Clutch " <i>De Bethune Patent (2014)</i> |
| Frequency: | 36,000 vibrations per hour |
| Adornment: | Bridges mirror-polished, sandblasted and snailed by hand Steel parts polished and chamfered by hand |



DE BETHUNE

L'ART HORLOGER AU XXI^e SIÈCLE

Display

| | |
|----------|--|
| Display: | 5 curved central hands – hand-polished and flame-blued steel for hours and minutes hands and chronograph and seconds indicators – chronograph minutes indicator in rose gold |
| Dial: | Three dimensional silver dial constructed on different levels to maximize readability. From the center to the periphery: central hours counter – hour ring – minutes ring and minutes counter – 1/10 th of second graduated outer ring for seconds counter Flame-blued, polished steel Arabic relief as hour markers |

Case and strap

| | |
|-------------------|--|
| Case material: | Mirror-polished grade 5 titanium |
| Case diameter: | 46 mm |
| Case thickness: | 11 mm |
| Lugs: | short or long floating lugs in mirror-polished grade 5 titanium – <i>De Bethune Patent (2006)</i> |
| Crystal: | In sapphire crystal (1800 Vickers hardness) with double anti-reflective coating |
| Case back: | Open on the mechanism with bridges and hand-polished steel parts Sapphire crystal (1800 Vickers hardness) with double anti-reflective coating |
| Water resistance: | 3 ATM |
| Strap: | Extra-supple alligator leather, alligator lining |
| Buckle: | Pin buckle in mirror-polished grade 5 titanium |