

DB25 Perpetual Calendar

Technical specifications





DB25 Perpetual Calendar

Technical specifications

Name: DB25 Perpetual Calendar

Reference: DB25QPAWS8

Functions: Hours, Minutes, Spherical moon phase indication

and leap-year indication at 12 o'clock, Perpetual calendar indicating the month at 3 o'clock, the date at 6 o'clock and the day of the week at 9 o'clock

Movement: DB2324

Type: Mechanical self-winding movement

Adjustment: Winding, setting the date and the time by means of

the crown (3 positions)

Month, day of the week and spherical moon phase

adjustment via correctors

Technical features of calibre DB2324

Number of parts: 425

Jewelling: 47 jewels Diameter: 44 mm

Power reserve: 5 days, ensured by a self-regulating twin barrel

De Bethune Innovation (2004)

Specificities:

studs

Titanium and platinum balance wheel with blom

De Bethune Patent (2008)

"De Bethune" balance-spring with flat terminal curve

De Bethune Patent (2006)

Silicon escape wheel

Spherical moon phase indication accurate to a degree of one lunar day every 122 years – De

Bethune Patent (2004)

Triple pare-chute shock-absorbing system

De Bethune Innovation (2005)

Optimized oscillating weight in titanium and white

gold

Oscillating weight shock-absorbing system

De Bethune Innovation (2006)

Frequency: 28,800 vibrations per hour



Adornment: 3/4 plate with starry decor, sandblasted and snailed

by hand

Balance bridge and oscillating weight arms in blued

titanium

White gold oscillating weight hand snailed Hand-polished, chamfered steel parts

Display

Display: Hands curved, in hand mirror-polished steel

Perpetual calendar apertures indicating the day of the week at 9 o'clock and the month at 3 o'clock – sub dial at 6 o'clock indicating the day of the month – leap year indicated by a gold pastille appearing in

the starry sky at 12 o'clock

Spherical moon phase indication in palladium and black oxide zirconium with an accuracy of one lunar day every 122 years at 12 o'clock – De Bethune

Patent (2004)

Dial: Anthracite hand-guilloché, with 12 radiating sectors

De Bethune star-studded sky in black steel, inlaid

with rose gold stars

Anthracite curved hour, date and moon phase rings

with silver relief Roman numerals

Case and strap

Case material: White gold Case diameter: 44 mm Case thickness: 11,1 mm

Lugs: Integrated, hollowed lugs

Crystal: In sapphire crystal (1800 Vickers hardness) with

double anti-reflective coating

Case back: Open back in polished white gold sapphire crystal

(1800 Vickers hardness) with double anti-reflective

coating

Water-resistance: 3 ATM

Strap: Extra-supple alligator leather, lining alligator

Buckle: Pin buckle in white gold